

特性与用途

相当规格

该焊丝适用于全位置TIG焊接，特别适用于薄板、小径管的焊接。在焊接过程中，焊丝熔化迅速，电弧稳定，焊缝成形美观，且具有良好的抗裂性能。

AWS: E308L-16 ER308LMo-4

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0

02U 5N100Z0